


Efficiency of ANP Measured - AppNote


Aqueous Normal Phase (ANP) Efficiency Measured with Sorbitol, Glucose & Uracil

Figure A is an excerpt from a study that investigated analyses of Glucose and Sorbitol on TYPE-C Silica based HPLC Columns and found that the efficiency of ANP is better than observed with HILIC. A Cogent Diamond Hydride Column (2.1 x 150mm with a Particle Size of 4μ m) was used and Flow Rate v. HETP was plotted as shown. From the plot it is evident that while the Flow Rate is increased by a factor of 2.5 the Efficiency is only slightly lower (\sim 15%).

A similar Cogent Diamond Hydride (4.6×150 mm and Particle Size of 4μ m) and a typical, commercially available HPLC Column designed for HILIC mode, (with equal specifications) were used to retain and separate Uracil under the same conditions. Figure B shows a plot of "Efficiency vs. Flow Rate" for both Columns. From the graph it can be seen that efficiency increases as the Flow Rate increases from 0.3 to 1.0mL / minute for the ANP Column while in contrast, the HILIC Column's efficiency dropped by more than 30% over this same range of Flow Rates.

It should be noted that linear Flow Rates are more than 6 times greater in the 2.1mm Column than in the 4.6mm.





Printed from the Chrom Resource Center Copyright 2024, All Rights Apply

MicroSolv Technology Corporation

9158 Industrial Blvd. NE, Leland, NC 28451

Figures: tel. (732) 380-8900, fax (910) 769-9435

A. Sorbitol, Glucose. On a Diamond Hydride Column Email: customers@mtc-usa.com

Website: www.mtc-usa.com



B. Uracil. DH and HILIC Column Comparison

Method Conditions

Columns:

Figure A: Cogent Diamond Hydride[™], 4μm, 100Å Figure B: Cogent Diamond Hydride[™], 4μm, 100Å

Catalog Nos.:

Figure A: 70000-15P-2 Figure B: 70000-15P

Dimensions:

Figure A: 2.1 x 150mm Figure B: 4.6 x 150mm

Mobile Phase:

A: DI Water / 0.1% Formic Acid
B: Acetonitrile / 0.1% Formic Acid
Flow rate: Variable, See Charts

Detection: UV (Uracil) and LCMS (Sorbitol, Glucose)

Injection vol.: 10µL

Notes: Charts and Methods are adapted from "Analysis of Hydrophilic Metabolites in Physiological Fluids by HPLC-MS using a Silica Hydride-Based Stationary Phase". J.J. Pesek, M.T. Matyska, J.A. Loo, S.M. Fischer, T.R. Sana, J. Sep. Sci., 32 (2009) 2200-2208.



Printed from the Chrom Resource Center Copyright 2024, All Rights Apply

MicroSolv Technology Corporation

9158 Industrial Blvd. NE, Leland, NC 28451 tel. (732) 380-8900, fax (910) 769-9435

Email: customers@mtc-usa.com

Website: www.mtc-usa.com